




European Expert Centre for Space Safety Providing Services and Support for Space Surveillance and Traffic Management

T. Schildknecht,
P. Pessev, P. Patole, and J. Rodriguez
*Astronomical Institute, University of Bern,
Switzerland*

T. Flohrer, B. Jilete, and E. Cordelli
ESA ESOC, Darmstadt, Germany

*22nd International Workshop on Laser
Ranging
7–31 November, 2022, Yebes, Spain*



Introduction

Expert Centre for Space Safety providing services and support for SST & STM

- Developed within ESA's Space Safety Program
- Hosted at the University of Bern, **AIUB**, Switzerland

Observing:


- Passive optical
- Active optical (SLR)
- Active microwave (RADAR)

Providing:

- Subject matter expertise
- Operational services
- Test services
- ...


Addressing:

- ESA
- Sensor owner/operator
- SST/STM service providers
- ...





Expert Centre Core Services






Space Safety Expert Centre Architecture







Expert Centre Stakeholders/Users





Expert Centre Network & Observation Types




- **Service Level Agreements**


- Unit prices
- License model
- KPIs


- **V & Q**

- Tracking
- Surveys
- Characterization



Expert Centre Network & Observation Types






Expert Centre Services


Single interface for user/customer

- Request
- Product delivery
- ...

High-level user requests

- OD & OI for tasked object
- Customized surveys
- Attitude estimation
- Astrometry/photometry
- ...





Service Example: Sensor V & Q

AIM:

Certify that a sensor can *reliably* provide data respecting defined *quality* criteria


1. Validation

- Establish the communication interfaces I/O
- Sensor is able to provide tracking data of the tasked objects
- Validate formats


2. Qualification

- 3 full observation nights (passive optical)/radar session
- 12 calibration objects and 4 program objects
(calibration objects: e.g. ILRS objects with fiducial orbits)


Data Validation Example




LAGEOS-1




Raw data




After corrections



After Tb & Rb




Measurement Quality




Nsec -> pulse width


Signal characterization




Data Qualification Example




Rocket body




Relative geometry



Raw data




After Tb & Rb





Example KPI for Sensor Qualification

- Examples of KPI for SLR sensors


Efficiency (%)	Objects successfully tracked and processed / Total # tasked objects
Time Bias (usec)	Estimated from single passes using observations to fiducial ILRS targets (next talk)
Range Bias (mm)	Estimated together with the Time Bias (next talk)
Number of Normal Points & RMS	Total number of normal points after detection, detrending and screening procedures
SNR per Normal Point	Ratio between returns classified as signal compared to the ones classified by noise / NP/ target



Example KPI for SLR Sensor Qualification







- Single passes only
- Outliers due to few normal points or poor relative geometry/length of observed pass
- Analysis of KPIs over time
- Stability & magnitude of KPIs → reliability & quality




Attitude Information Service

- Maintenance of **attitude information catalogue**
- **Planning, scheduling, acquisition, and processing** of the basic observation (light curves, SLR, ...)
- Automated **attitude type characterization** (“stabilized”, “slow rotator”, “fast rotator”)
- Estimation of **rotation/tumbling rates**

Type of Light Curves







Providing Subject–Matter Expertise

Example



- Validation of IZN–1 observations (Experts, Bernese s/w)
(CODE MGEX satellite orbits, ...)





Research and Development (Examples)


discrimination of laser returns




Data Fusion

ENVISAT

SLR range residuals



light curve



Take Home

The ESA/AIUB ExpCen for Space Safety provides a multitude of services in support of SST and STM:

- Sensors: passive optical, debris SLR, tracking radar
- Coordination of observation campaigns for customers
- Qualification of sensors
- Attitude information service
- Subject matter expertise
- ...

A bright blue light streak curves diagonally from the top-left corner towards the bottom-right corner of the frame. The background is a deep, dark black. In the middle-right section of the image, a small, thin crescent moon is visible, appearing to be positioned just above the light streak.

Thank you for your time!