



WROCŁAW UNIVERSITY OF ENVIRONMENTAL AND LIFE SCIENCES

2017 ILRS Technical Workshop

"Improving ILRS Performance to meet Future GGOS Requirements"

October 02-05, 2017, Riga, University of Lativa

How many SLR observations and how many station are needed for deriving high-quality multi-GNSS orbits?

Grzegorz Bury, Krzysztof Sośnica

Institute of Geodesy and Geoinformatics, Wrocław University of Environmental and Life Sciences grzegorz.bury@igig.up.wroc.pl

The goal of this study

This presentation aims at addressing the following questions:

- How does the number of SLR observations act on the multi-GNSS orbit accuracy determined using solely SLR data?
- 2. What is an optimal geometry of SLR observations, thus how many SLR stations are needed to determine precise multi-GNSS orbit?
- Can we develop a common strategy for multi-GNSS orbit determination using SLR data?

Number of SLR observations to multi-GNSS (2014.0-2017.4)



Number of SLR observations to multi-GNSS



CES

Processing scheme of parameter estimation using range measurements to multi-GNSS



Multi – GNSS orbitsSLR station coordinatesGeocenter coordinatesEarth Rotation ParametersOrbit validationTime transfer

Multi-GNSS orbit determination using slolely SLR data and comparison with a priori CODE-MGEX products (test 3-, 5-, 7- and 9-day arcs)

Analysis period: 2014.0 – 2016.9

The efficiency of the 3-day solutions



Due to poor geometry (1-2 tracking stations) the efficiency is poor as well

Detailed 3-day solutions

Fig. A detailed 3-day solutions provided from a high number of SLR observations: 110 (right), 54 (middle), and an insufficient number of SLR observations: 25 (left) for GLONASS R18. RMS presented for the middle day (time in UTC) of the solution.





For intensively tracked satellites 60 SLR observations are needed to determine precise orbit at the level of 3 cm in the radial direction,

The effort should be put on the homogenous tracking of the whole multi-GNSS constellation,

Due to the regional attitude of BeiDou IGSO and QZSS, the number of observations is insufficient,



- The geometry of observations provided by 5 stations is insufficient to determine a reliable orbit,
- The increase of the number of stations from 5 to 10 reduces steadily RMS to the level of: 3, 8, and 15 cm in the radial, along-track, and cross-track direction, respectively,
- The poor geometry of BeiDou IGSO and QZSS is caused by regional attitude of those constellations,

Geometry of observations

- The best solution was obtained for GLONASS R07 at 15 July 2015 (5-day solution)
- Number of observation: 129
- 12 evenly located SLR stations
- RMS: 0.8, 2.4 and 1.9 cm in the radial, along-track and cross-track direction, respectively



• 60 observations are sufficient to determine orbit of an average quality.

Median RMS of differences between SLR and microwave derived multi-GNSS orbits. All values in cm.

Component	GLONASS	Ga	lileo	Bei	QZSS	
		IOV	FOC	MEO	IGSO	
Radial	2.9	4.0	4.3	2.3	4.6	-
Along-track	8.8	10.4	15.7	10.2	24.5	-
Cross-track	16.7	18.1	20.3	12.3	49.8	-
3D	21.4	23.3	26.2	17.9	55.6	-

Recomendation: At least 100 observations provided by at least 10 evenly located stations

Summary

- 60 SLR observations are sufficient to determie mulit-GNSS orbit of an average quality (for inactive satellites). Orbits calculated from ca.100 SLR observations are at the cm-level accuracy,
- Orbits provided by more than 10 evenly distributed SLR stations are at the cm-level of accuracy,
- However, we need observations collected by stations not only from Europe and Australia, but also from N&S America and Asia, especially if considering BeiDou IGSO and QZSS.

Thank You for Your Attention



WROCŁAW UNIVERSITY OF ENVIRONMENTAL AND LIFE SCIENCES



Grzegorz Bury grzegorz.bury@igig.up.wroc.pl Institute of Geodesy and Geoinformatics <u>http://www.igig.up.wroc.pl/igg/</u>

Scheduling according to observation geometry (?)

Europe – a lot of high-performing stations: Station Group 1: 7810, 7941, 7824, 7811, 1874 Station Group 2: 7839, 8834, 7841, 1884, 1886 Station Group 3: 7840, 7827, 7845, 1837, 1888

Australia:	
Station Group 1:	7090
Station Group 2:	7825

N&S America, Africa, Pacific

Should track everything following the ILRS list

	Day 1	Day 2	Day 3
GLONASS plane I	Group I	Group II	Group III
GLONASS plane II	Group II	Group III	Group I
GLONASS plane III	Group III	Group I	Group II

	Day 1	Day 2
GLONASS plane I	Group I	Group II
GLONASS plane II	Group II	Group I
GLONASS plane III	Group II	Group I

The discussion of the results



The accuracy of SLR-derived orbits depends on: (1) the number of SLR observations, (2) the number and distribution of SLR tracking stations, (3) the length of the orbital arc, (4) the generation of the satellite, (5) type of an orbital plane, (6) β angle, (7) and empirical models used in the calculation (ECOM1/ECOM2).

Number of observations







System	GLON	IASS		Galileo		BeiDou		QZSS			
Туре	GLONASS-M	GLONASS-K	IOV	FOC (extended orbit)	FOC	MEO	IGSO	GEO	QZS-1/2 (IGSO)	QZS-3 (GEO)	50 000 km
PRN Number	R01-R08 R10-R19 R21-R24	R09, R20 (spare)	E11, E12, E19, E20	E14, E18	E26, E22, E24, E30, E08, E09, E01, E02, E07, E03, E04, E05	C11, C12, C14, C33, C34 , C35	C06-C10, C15, C31, C32, C13	C01-C05, C17	J01, J02	J03	40 000 QZSS BeiDou IGSO/GEO
CODE products	ALL	ALL	E11, E12, E19	ALL	ALL	C11-C14	C06-C10, C15	-	J01	-	30 000 - Galileo extended
ILRS tracking	ALL	ALL	ALL	ALL	ALL	C11, C33, C34	C08, C10, C15, C31, C32	C01	J01, J02	J03	20 000 GI ONASS
Retroreflec tors	112	123	84	60	60	42	42	90	56	56	
Size of LRA [mm]	311.0/510.8	O: 633.7, I: 342.5	430.0/ 470.0	331.0/ 248.7	331.0/ 248.7	316.0/ 280.0	316.0/ 280.0	490.0/ 430.0	400.0/ 400.0	400.0/ 400.0	10 000
Mass [kg]	1 415	935	695-697	661/662	706-709	1 900	1 900	1 550	1 896/ 1 550	1 700	LAGEOS-1/2
Altitude [km]	19 132	19 132	23 225	17 178 - 26 019	23 226	21 529	35 790	35 790	32 000 – 40 000	36 000	Earth
Orbit	MEO	MEO	MEO	MEO	MEO	MEO	Geosynch.	Geostat.	Geosynch.	Geostat.	
Inclination [deg]	64.8	64.8	54.9- 55.6	50.1	54.9-57.2	56.2	53.3-57.7	0.9-1.6	40.7	0.0	IVERSITY FE SCIENCES

Statistics





- The geometry of observations provided by 5 stations is insufficient to determine a reliable orbit,
- The increase of the number of stations from 5 to 10 reduces steadily RMS to the level of: 3, 8, and 15 cm in the radial, along-track, and cross-track direction, respectively,

Multi-GNSS EXperiment

QZSS

Multi-

GNSS

Beilou



Analysis centers:

- Centre National d'Etudes Spatiales (CNES), Collecte Localisation Satellites (CLS),
- Center for Orbit Determination in Europe (CODE)
- GeoForschungsZentrum Potsdam (GFZ)
- Technische Universität München (TUM)
- Japan Aerospace Exploration Agency (JAXA)
- Wuhan University

Fig The networks of MGEX tracking stations on day: 10.01.2017 http://www.igs.org/network?network=multi-GNSS

Data centers:

- Crustal Dynamics Data Information System (CDDIS)
- Institut Géographique National (IGN)
- Bundesamt f
 ür Kartographie und Geod
 äsie (BKG)

Products:

- **Precise Orbits** and Clock Products
- Broadcast Ephemerides
- Differential Code Biases
- Real-Time Products

JASS

ilec

G

Station coordinates – repeatability improvement when including SLR@GNSS (see poster session)



Zelenchuksakya (Russia) :

RMS: 49.6 56.3 27.9 mm for North, East, Up, resp. in LAGEOS-1/2 RMS: 21.6 18.4 15.4 mm for North, East, Up, resp. in LAGEOS+GNSS fix 108 solutions in LAGEOS-1/2 123 solutions in LAGEOS+GNSS (14% more solutions) Arkhyz (Russia) :

RMS: 77.2 30.2 94.7 mm for North, East, Up, resp. in LAGEOS-1/2 RMS: 28.0 22.3 19.9 mm for North, East, Up, resp. in LAGEOS+GNSS fix 100 solutions in LAGEOS-1/2

139 solutions in LAGEOS+GNSS (39% more solutions)