

ILRS SLR MISSION SUPPORT REQUEST FORM (June 2011)

SECTION I: MISSION INFORMATION:

General Information:

Satellite Name: _____

Satellite Host Organization: _____

Web Address: _____

Contact Information:

Primary Technical Contact Information:

Name: _____

Address: _____

Phone No.: _____

Fax No.: _____

E-mail Address: _____

Alternate Technical Contact Information:

Name: _____

Address: _____

Phone No.: _____

Fax No.: _____

E-mail Address: _____

Primary Science Contact Information:

Name: _____

Address: _____

Phone No.: _____

Fax No.: _____

E-mail Address: _____

Alternate Science Contact Information:

Name: _____

Address: _____

Phone No.: _____

Fax No.: _____

E-mail Address: _____

Mission Specifics:

Scientific or Engineering Objectives of Mission:

Satellite Laser Ranging (SLR) Role of Mission:

Anticipated Launch Date: _____

Expected Mission Duration: _____

Orbital Accuracy Required: _____

Anticipated Orbital Parameters:

Altitude: _____

Inclination: _____

Eccentricity: _____

Orbital Period: _____

Frequency of Orbital Maneuvers: _____

Mission Timeline: _____

Tracking Requirements:

Tracking Schedule: _____

Spatial Coverage: _____

Temporal Coverage: _____

Operations Requirements:

Prediction Center: _____

Prediction Technical Contact Information:

Name: _____

Address: _____

Phone No.: _____

Fax No.: _____

E-mail Address: _____

Priority of SLR for POD: _____

Other Sources of POD (GPS, Doppler, etc.):

Normal Point Time Span (sec): _____

Tracking Network Required (Full/NASA/EUROLAS/WPLTN/Mission Specific):

SECTION II: TRACKING RESTRICTIONS:

Several types of tracking restrictions have been required during some satellite missions. See http://ilrs.gsfc.nasa.gov/satellite_missions/restricted.html for a complete discussion.

- 1) Elevation restrictions: Certain satellites have a risk of possible damage when ranged near the zenith. Therefore a mission may want to set an elevation (in degrees) above which a station may not range to the satellite.
- 2) Go/No-go restrictions: There are situations when on-board detectors on certain satellites are vulnerable to damaged by intense laser irradiation. These situations could include safe hold position or maneuvers. A small ASCII file is kept on a computer controlled by the satellite's mission which includes various information and the literal "go" or "nogo" to indicate whether it is safe to range to the spacecraft. Stations access this file by ftp every 5-15 minutes (as specified by the mission) and do not range when the flag file is set to "nogo" or when the internet connection prevents reading the file.
- 3) Segment restrictions: Certain satellites can allow ranging only during certain parts of the pass as seen from the ground. These missions provide station-dependent files with lists of start and stop times for ranging during each pass.
- 4) Power limits: There are certain missions for which the laser transmit power must always be restricted to prevent detector damage. This requires setting laser power and beam divergence at the ranging station before and after each pass. While the above restrictions are controlled by software, this restriction is often controlled manually.

Many ILRS stations support some or all of these tracking restrictions. See xxx for the current list. You may wish to work through the ILRS with the stations to test their compliance with your restrictions or to encourage additional stations that are critical to your mission to implement them.

The following information gives the ILRS a better idea of the mission's restrictions. Be aware that once predictions are provided to the stations, there is no guarantee that forgotten restrictions can be immediately enforced.

Can detector(s) or other equipment on the spacecraft be damaged or confused by excessive irradiation, particularly in any one of these wavelengths (532nm, 1064nm, 846nm, or 423nm)?

Are there times when the LRAs will not be accessible from the ground?

(If so, go/nogo or segmentation files might be used to avoid ranging an LRA that is not accessible.)

Is there a need for an altitude tracking restriction? _____ What altitude (degrees)? _____

Is there a need for a go/no-go tracking restriction? _____

For what reason(s)?

Is there a need for a pass segmentation restriction? _____

For what reason(s)?

Is there a need for a laser power restriction? _____

Under what circumstances?

What power level (mW/cm²)? _____

Is manual control of transmit power acceptable? _____

For ILRS stations to range to satellites with restrictions, the mission sponsor must agree to the following statement:

“The mission sponsor agrees not to make any claims against the station or station contractors or subcontractors, or their respective employees for any damage arising from these ranging activities, whether such damage is caused by negligence or otherwise, except in the case of willful misconduct.”

Please initial here to express agreement: _____

Other comments on tracking restrictions:

SECTION III: RETROREFLECTOR ARRAY INFORMATION:

A prerequisite for accurate reduction of laser range observations is a complete set of pre-launch parameters that define the characteristics and location of the LRA on the satellite. The set of parameters should include a general description of the array, including references to any ground-tests that may have been carried out, array manufacturer and whether the array type has been used in previous satellite missions. So the following information is requested:

Retroreflector Primary Contact Information:

Name: _____

Address: _____

Phone No.: _____

Fax No.: _____

E-mail Address: _____

Array type (spherical, hexagonal, planar, etc.), to include a diagram or photograph:

Array manufacturer:

Link (URL or reference) to any ground-tests that were carried out on the array:

The LRA design and/or type of cubes was previously used on the following missions:

For accurate orbital analysis it is essential that full information is available in order that a model of the 3-dimensional position of the satellite center of mass may be referred to the location in space at which the laser range measurements are made. To achieve this, the 3-D location of the LRA phase center must be specified in a satellite fixed reference frame with respect to the satellite's mass center. In practice this means that the following parameters must be available at mm accuracy or better:

The 3-D location (possibly time-dependent) of the satellite's mass center relative to a satellite-based origin:

The 3-D location of the phase center of the LRA relative to a satellite-based origin:

However, in order to achieve the above if it is not directly specified (the ideal case) by the satellite manufacturer, and as an independent check, the following information must be supplied prior to launch:

The position and orientation of the LRA reference point (LRA mass-center or marker on LRA assembly) relative to a satellite-based origin:

The position (XYZ) of either the vertex or the center of the front face of each corner cube within the LRA assembly, with respect to the LRA reference point and including information of amount of recession of front faces of cubes:

The orientation of each cube within the LRA assembly (three angles for each cube):

The shape and size of each corner cube, especially the height:

The material from which the cubes are manufactured (e.g. quartz):

The refractive index of the cube material, as a function of wavelength λ (micron):


Dihedral angle offset(s) and manufacturing tolerance:

Radius of curvature of front surfaces of cubes, if applicable:

Flatness of cubes' surfaces (as a fraction of wavelength):

Whether or not the cubes are coated and with what material:

The Position of the Compass-M3 Laser Retro-Reflector Array Phase Center



Vector C is from the satellite coordinate origin to the satellite's center of mass (CoM).

Vector L is from the satellite coordinate origin to the mass center of the LRA containing 42 corner cubes.

$$C = (1082.0, -0.4, -0.5) \text{ mm} .$$

$$L = (649.9, -562.5, 1133.3) \text{ mm}.$$

The plane of the front faces of the cubes is +14.0 mm in the Z direction from the LRA mass center.

The cubes' phase centers are $-h \times n$ in the Z direction from the plane of the cubes.

For the Compass-M3 cubes, $h = 24.0$ mm, $n = 1.46$. So phase centers are - 35.0 mm in Z.

So z-component of array phase center is $(-35.0 + 14) = - 21.0$ mm from the LRA mass center.

Let L' as the vector from the satellite coordinate origin to the phase center of the LRA. We have

$$L' = (649.9, -562.5, 1133.3 - 21.0) = (649.9, -562.5, 1112.3) \text{ mm}$$

Finally, the vector CP from the satellite center of mass to the phase center of the LRA is

$$CP = L' - C$$

So $CP = (649.9, -562.5, 1112.3) - (1082.0, -0.4, -0.5) = (-432.1, -562.1, 1112.8)$ mm in the satellite fixed frame.

SECTION IV: MISSION CONCURRENCE

As an authorized representative of the _____ mission, I hereby request and authorize the ILRS to track the satellite described in this document.

Name (print): _____ Date _____

Signature: _____

Position: _____

Send form to: ILRS Central Bureau
c/o Carey Noll
NASA GSFC
Code 690
Greenbelt, MD 20771
USA
301-614-6542 (Voice)
301-614-6015 (Fax)
Carey.Noll@nasa.gov